


Combined CO₂ & Temperature Transmitter: CS-CO2-03

CaterSense® - combined CO₂ and temperature transmitter is used in conjunction with the CaterSense range and for the control of natural ventilation applications to control the temperature and CO₂ levels within a given space.

The transmitter has 2 x 0~10v analogue outputs which are linear in respect of the range of detection.



Model Type	Model	Description
	CS-CO2-03	CO ₂ & Temperature transmitter
Technical Data	Power supply	24Vac / dc
	Dimensions	100 mm x 85 mm x 26 mm (Wt: 110g)
Wiring Terminals	1	+24Vac / dc
	2	0 volt ac / dc
Range: 0~5000ppm	5	0~10vdc (CO ₂ output)
Range: 0 ~ 50°C	4	0~10vdc (Temperature output)




Mounting

Install in a clean environment in an area with good air movement.

Recommended mounting height 1.5 - 2m from floor.

Avoid areas of localised heat, windows, doors etc.

Dimensions



To remove front cover press centre tab with a small screwdriver and pull bottom away from the backplate



This symbol on this product or the package indicates that disposal of this product after its lifecycle could harm the environment. DO NOT dispose of this product (or batteries if used) as unsorted municipal waste. It should be disposed by a specialised company for recycling. This product should be returned to your distributor or to a local recycling service. Respect the local environment rules.